



B0519-2

3 Ply Basic Medical Face Mask

PHYSICAL DIMENSION

DESIGN	THICKNESS	
Outer Layer	Fluid Resistance PP	30 gsm
Middle Layer	Melt blown Filter	25 gsm
Inner Layer	PP Non Woven & Water Absorbent	25 gsm

Product Specification & Instruction Use

PRODUCT SPECIFICATIONS:

Classification:
Type I
MDA No: GA43088421-58036

Product Material:
Non-woven fabric

Packaging Mode:
50 pcs per box / 20 boxes per carton

Physical Features

- Hypoallergenic
- Reduce the spread of pathogen
- Comfortable Lining
- Single Use Only

STORAGE:

- Store in dry, clean conditions in original packaging.
- Store away from direct sunlight, source of high temperature and solvent vapors.
- Store with the temperature range 0°C to 39°C
- Shelf life is 60 months from the date of manufacture when stored as stated above.
- Replace if damaged or heavily contaminated.
- Dispose of contaminated face mask with care and in accordance with national regulations.

3 Ply Layer Mask Filter



EN 14683:2019 Type I

Bacterial Filtration Efficiency (BFE)	≥ 95%
Differential Pressure	<40 Pa/cm ²
Splash Resistance Pressure	Not required
Microbial Cleanliness	≤ 30 cfu/g

Instruction:



1. Place loop over the ears.
2. Ensure coloured layer to face out.
3. Adjust nose piece for comfort fit.



- More Breathable**
- 3 Layers Protection**
- Fluid Resistance**
- >95% BFE**



USE LIMITATIONS (Do not use for):

- Contact with heavy oils, sparks or flames
- Environment with conditions of excessive heat.



Bergamot Sdn Bhd (1153028-V)
No 7 & 8, Jalan Sinaran 6,
Kawasan Perindustrian Sinaran,
43000 Kajang, Selangor,
Malaysia

info@bergamot.com.my
+603 8964 4186